

LCD Digital Clocks with Date Line

ideal for prestigious rooms and places of high publicity

LCD digital clocks with date line, sturdy case, available in silver or white. High definition, high contrast LCD display for outstanding readability even at extremely sharp angles.

Case

Extra flat, sturdy plastic case enamelled metallic silver as standard. White enamel is optional without surcharge.

LCD digital display

2-line LCD display with extra large black 9-segment ciphers, top line showing hours and minutes (4 digits, cipher height 74 mm), bottom line showing the date (6 digits, cipher height 54 mm), optionally with abbreviated day-of-week (2 characters). Optionally, room temperature may be displayed alternating with time or date.



71.560.791 shown

Technical data		
Case	colour	silver, white (option)
	dimensions (W x H x D)	cir. 378 x 258 x 35 mm
Display	cipher height hours/minutes	74 mm
	character height date	54 mm
	reading distance	cir. 20 m
Weight		cir. 1.3 kg

Clock type	Item No.	€ each
DCF77 radio controlled clock, battery operated 1.5 V	51.560.791	699.-
DCF77 radio controlled clock, mains operated 230 VAC	52.560.791	789.-
Slave clock, minute pulse 12/24 V ¹⁾	71.560.791	769.-
Telegram slave clock, DCFport24, 12/24 V ²⁾	81.560.791	769.-

Accessory	Item No.	€ each
External DCF77 receiving aerial (IP 31), for radio controlled types (required only if reception quality is poor)	03.925.171	110.-

Options	Suffix	Surcharge € each
Case custom enamelled	-10	on request
Integrated power supply for 230 VAC mains operation instead of battery operation (on clock type 71.xxx only)	-69	98,-
Abbreviated day-of-week in date line (2 digits)	-90	65,-
Alternating room temperature display (internal temperature sensor)	-91	69,-
Alternating room temperature display (external temperature sensor, IP 31)	-92	99,-



71.560.791 -90

¹⁾Operation of the LCD display requires batteries (LR 6/AA type, included in delivery shipment) or an integrated power supply (optional).

²⁾Operating voltage is supplied by the master clock via DCFport24 telegram (current draw cir. 10 mA).



Indoor digital single-sided

Type series

560



DCF77 radio controlled clocks

DCF77 radio controlled clocks will only function correctly within a radius of approx. 1,500 km around Mainflingen (50 km east of Frankfurt/M.) and under conditions of free radio propagation and may be impaired in heavily reinforced concrete structures. For this case we recommend a remotable DCF77 aerial (option).

PEWETA DCFport24

PEWETA DCFport24 slave clocks require a PEWETA master clock (see from page 174 on).