

Wall Clocks

single face

Sensible, matter-of-fact clocks in a trendy design. Unambiguous, functional, up-to-date.

Case

■ cir. 290 mm diameter
shock-resistant plastic, grey (close to RAL 7035).
Protection grade IP 40 (EN 60529).

Front glass

Shock-resistant clear plastic.

Face

High distinction white metal with black DIN bar or fine-line markings for easy, doubt-free reading even over longer distances. Face printed according to DIN 41091.

Hands

Black bar-type hour and minute hands, red second hand.

No second hand on minute pulse 12...60 V controlled slave clocks.



21.260.221 shown



Indoor
analog
single face

Type series

260



| Clock type | Bar markings Item No. | € each | Fine line markings Item No. | € each |
|--|--------------------------|---------------|--------------------------------|---------------|
| Synchronous clock, mains op. 230 VAC/50 Hz | 21.260.221 | not available | 21.260.231 | not available |
| Quartz clock, battery operated 1.5 V | 41.260.221 | not available | 41.260.231 | not available |
| DCF77 radio controlled clock, battery operated 1.5 V | 51.260.221 | not available | 51.260.231 | not available |
| DCF77 radio controlled clock, mains operated 230 VAC, with outage reserve | 52.260.221 | not available | 52.260.231 | not available |
| Slave clock, minute pulse 12...60 V | 71.260.221 | not available | 71.260.231 | not available |
| Slave clock, minute/second pulse 12/24 V | 72.260.221 | not available | 72.260.231 | not available |
| Slave clock, DCFport24 pulse telegram | 81.260.221 | not available | 81.260.231 | not available |
| Slave clock, AirPort24 radio controlled telegram, battery operated 1.5 V | 84.260.221 | not available | 84.260.231 | not available |
| Slave clock, AirPort24 radio controlled telegram, mains op. 230 VAC, with outage reserve | 85.260.221 | not available | 85.260.231 | not available |
| Slave clock, NTP synchronisation by LAN (NTP client), PoE ¹⁾ | 91.260.221 | not available | 91.260.231 | not available |

| Option | Suffix | Surcharge € each | Suffix | Surcharge € each |
|---|--------|---------------------|--------|---------------------|
| External DCF77 receiving aerial (cannot be added later) | -60 | not available | -60 | not available |

DCF77 radio controlled clocks

DCF77 radio controlled clocks will only function correctly within a radius of approx. 1,500 km around Mainflingen (50 km east of Frankfurt/M.) and under conditions of free radio propagation and may be impaired in heavily reinforced concrete structures. For this case we recommend a removable DCF77 aerial (option).

PEWETA DCFport24

PEWETA DCFport24 slave clocks require a PEWETA master clock (see from page 184 on).

PEWETA AirPort24

PEWETA AirPort24 slave clocks require an AirPort24 transmitter or repeater respectively (see page 189).

NTP

NTP slave clocks require an NTP time server (see page 191).



41.260.231

¹⁾ NTP slave clocks of "PoE" type require a PoE (Power over Ethernet) power supply. Appropriate hardware has to be supplied by customer.