

Clocks for Large Spaces

on-wall mounting, indoor



Large space
analog
single face

Type series

370



Also available
"resistant
to thrown balls"



21.370.511 shown

Clocks of this type series are excellently suited for all applications requiring large clocks with **solid, industrial grade metal cases** combined with a doubt-free readability.

They are also available "resistant to thrown balls" according to DIN 18032, part 3.



21.370.511 -22

▲ Clock cases made of stainless steel V4A, blasted and varnished (optional) are resistant to saline or chlorous media. Excellently suited for permanent use in public swimming pools.

Case

- cir. 400x400 mm
- cir. 500x500 mm
- cir. 600x600 mm

very sturdy metal case, enamelled white (RAL 9016). Optionally, at a surcharge, custom enamelled, as listed below. A stainless steel case (1.4301 X5CrNi 18-10, German trade name V2A) with a matted finish or a stainless steel case (1.4571 X6CrNiMoTi 17-12-2, German trade name V4A), blasted and additionally coated with a protective varnish, are available as options. Protection grade IP 40 (EN 60 529).

Resistance to thrown balls acc. to DIN 18 032, part 3 (option)

Clocks of this type series are also available resistant to thrown balls and thus suitable for schools, gymnasiums and other sporting facilities. Very sturdy metal case with 6 mm two-ply laminated mineral safety glass. These clocks conform to German Industry Standard and are certified and

labelled "resistant to thrown balls according to DIN 18 032, part 3".

Front glass

Flat shock-resistant Plexiglas® XT (PMMA) as standard.

Packaging (option)

As an option, clockwork packaged to protect it against blown dust and/or sprayed water (IP 54 according to EN 60 529) is available.

Face

High distinction white metal with large black Arabic numerals for easy, doubt-free reading even over longer distances. Visible print diameters are 335 mm, 420 mm, and 503 mm respectively. Face printed according to DIN 41 091.

Hands

Black bar-type hour and minute hands. Red second hand on synchronous clocks (21.xxx), slave clocks with minute/second pulse (72.xxx) and slave clocks with synchronous second hands (74.xxx) only.

Plexiglas® XT


Plexiglas® XT is i. a. suited for use in food-processing plants.

Stainless steel V2A (option)

Due to its components stainless steel V2A is an alloy almost completely impervious to detergents and disinfectants and is therefore excellently suited for the use in the food and pharmaceutical industries, in kitchens, laboratories and other clean rooms. And it looks good into the bargain, as well!

Stainless steel V4A + varnish (option)

V4A quality stainless steel with an additional coat of protective varnish is outstandingly resistant to acids and other chlorurous media and is therefore particularly suited for public swimming pools as well as for the chemical industry.



Large space analog single face

Type series

370



DCF77 radio controlled clocks

DCF77 radio controlled clocks of this type series will be supplied including a removable DCF77 aerial (IP 68). Thus, optimum reception quality can be achieved regardless of the final placement of the clock itself. However, DCF77 radio controlled clocks will only function correctly within a radius of approx. 1,500 km around Mainflingen (50 km east of Frankfurt/M.).

PEWETA DCFport24

PEWETA DCFport24 slave clocks require a PEWETA master clock (see from page 184 on).

PEWETA AirPort24

PEWETA AirPort24 slave clocks require an AirPort24 transmitter or repeater respectively (see page 189).

NTP

NTP slave clocks require an NTP time server (see page 191).

Clock type	Face dimensions ▶	400 x 400 mm		500 x 500 mm		600 x 600 mm	
		Item No.	€ each	Item No.	€ each	Item No.	€ each
Synchronous clock, mains operated 230 VAC/50 Hz		21.370.411	365.–	21.370.511	445.–	21.370.611	565.–
DCF77 radio controlled clock, battery operated 2 x 1.5 V ¹⁾²⁾		51.370.411	358.–	51.370.511	729.–	51.370.611	839.–
DCF77 radio controlled clock, mains operated 230 VAC ²⁾		52.370.411	436.–	52.370.511	768.–	52.370.611	878.–
Slave clock, minute pulse 12...60 V		71.370.411	349.–	71.370.511	429.–	71.370.611	549.–
Slave clock, minute/second pulse 12/24 V		72.370.411	554.–	72.370.511	634.–	72.370.611	754.–
Slave clock, minute pulse 12/24 V, synchronous second hand 230 VAC/50 Hz		74.370.411	739.–	74.370.511	819.–	74.370.611	939.–
Slave clock, DCFport24 pulse telegram 24 V		81.370.411	368.–	81.370.511	509.–	81.370.611	619.–
Slave clock, AirPort24 radio controlled telegram, battery operated 2 x 1.5 V ¹⁾		84.370.411	466.–	84.370.511	629.–	84.370.611	739.–
Slave clock, AirPort24 radio controlled telegram, mains operated 230 VAC		85.370.411	526.–	85.370.511	668.–	85.370.611	778.–
Slave clock, NTP synchronisation by LAN (NTP client), PoE ³⁾		91.370.411	533.–	91.370.511	739.–	91.370.611	849.–

Options	400x400mm Suffix	Surcharge € each	500x500mm Suffix	Surcharge € each	600x600mm Suffix	Surcharge € each
Case enamelled in metallic silver grey RAL 9006	-05	34.–	-05	40.–	-05	49.–
Case enamelled in metallic dark gun metal DB 703	-06	34.–	-06	40.–	-06	49.–
Case custom enamelled	-10	on request	-10	on request	-10	on request
Case stainless steel V2A, matted finish	-20	390.–	-20	450.–	-20	490.–
Case stainless steel V4A, blasted and varnished	-22	550.–	-22	610.–	-22	650.–
Custom logo on clock face	-47	on request	-47	on request	-47	on request
Packaging against dust and spray (IP 54)	-54	80.–	-54	80.–	-54	80.–
Resistance to thrown balls acc. to DIN 18032, part 3	-59	169.–	-59	169.–	-59	169.–
External DCF77 receiving aerial (cannot be added later)	-60	149.–	fitted as standard		fitted as standard	

Options – just as you like them ...

These clocks are available optionally with customised features at the surcharges as listed. Just pick your option(s) and add the appropriate suffix(es) to the Item No.

Case colour	Suffix
metallic silver grey RAL 9006	-05
dark gun metal DB 703	-06
custom enamelled	-10
stainless steel V2A	-20
stainless steel V4A + clear varnish	-22

¹⁾ Alkaline batteries are included in delivery shipment (medium lifespan: cir. 4 years).

²⁾ A removable DCF77 receiving aerial is included in delivery shipment.

³⁾ NTP slave clocks of "PoE" type require a PoE (Power over Ethernet) power supply. Appropriate hardware has to be supplied by customer.

All prices are subject to change without notice, packing and shipping cost (see page 203) as well as VAT for deliveries within Germany added. Prices shown as of January 1st, 2017. If you desire additional information, please ask for the detailed type information sheet, quoting the Item Number. Alternatively, access our product data file on the Internet at www.peweta.com.